



Revision:

Overcoated with: All conventional base paints, water-based paints, lacquers and uni varnish based on the market.

The surface should be dry, clean, grease-free and completely free from impurities. Pretreated steel sheets, aluminum and galvanized metal sheets for cars should also be cleaned. For aluminum and galvanized sheets we recommend to spatterdash a wash primer.

It is highly recommended to work in the system. When using non-system dilution and hardener materials drying and adhesion problems can not be excluded.

:: SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

2K-varnish reacts with humidity. Therefore, all processing equipment, mixing vessels etc. must be free from water. Ready for processing paint materials containing isocyanate can exert a particularly irritating to the mucous membranes of the respiratory system and cause hypersensitivity reactions. By inhalation of vapor or spray mist there is the risk of sensitization. When dealing with products containing isocyanates all measures for solvent based coating materials must be strictly observed. Do not inhale sprayed mist and vapors. Allergic person, asthmatic and people who are prone to respiratory problems, must not be used for work with products containing isocyanates.

We reserve the right to update or complement the content of the information without prior notice and without obligation to actualisation at all times.

These provisions apply to the changes and additions continued unrestricted.

Copyright VOSSCHEMIE